


BUILDING A CUSTOM MAT PATTERN

- you will need
- paper
 - writing utensil
 - scissors
 - tape
 - ruler

flip for instructions »

1



BUILD A PATTERN

Measure the width and length of the floor where you would like your mat and cut a piece of paper slightly larger than these measurements. Place the paper into the car floor and mold it into the sides — pushing hard enough to make a crease in the paper. Take out the paper and cut 1/4 inch inside the crease marks and round the corners (our mats have a 1/4 inch growth rate.) Put your new pattern back into the car and adjust the fit using scissors to remove coverage or extra paper with tape to extend the coverage. Repeat for all mats.

2




MAT ATTACHMENTS

If your vehicle has floor mat attachments (via posts, twists, snaps, or velcro), draw a small circle at the exact location of each attachment on the pattern. If a pattern has two attachments, measure the distance between the exact center of each circle and write the measurement on the pattern. If your car has velcro attachments, write "velcro" next to the drawn circle.

Scan QR for attachment information




3



HEEL PAD LOCATION

For heel pad location, place the "X" sticker (provided) on the driver pattern where your heel hits the pattern while driving. No heel pad may be requested by writing "no heel pad" on the driver pattern.


4



LABELING YOUR PATTERN

For the accurate pattern direction, write your name on the top side of all paper patterns. On this same side, write where the front, back, left, and right locations are on the pattern.

5



CONFIRM AND MAIL

Confirm steps 1 - 4. Once completed, use the enclosed envelope to mail us your modified pattern.

CocoMats.com Attn:Patterns
236 Zimmer Rd.
Fort Mill, SC 29707

For more information, please visit www.cocomats.com/patterns
email: patterns@cocomats.com phone: 704-241-3897